


DX1 II

Quick Start Guide


1. Get to know your DAC



2. Connect to input source

USB Input: Connect to a computer for data transfer and power supply to the DX1 II. When connecting a device with insufficient power, such as a phone or Nintendo Switch, use a USB Y-cable (not included) to connect the DX1 II to the signal source and an external power supply.

Optical Input: Connect to an optical source; USB DC 5V power is required.




3. Connect the output device

3.1 Connect to amplifier or active speakers

You can connect the DX1 II via its RCA single-ended output or 4.4mm balanced stereo output.


To prevent potential damage, please ensure the power amplifier or active speakers are turned off before making connections.



3.2 Optical output

The DX1 II also features an optical output, allowing connection to external devices such as DACs.

Note: The optical output volume is fixed at maximum by default and cannot be adjusted. Please lower the volume of other devices first. To adjust the optical output volume, refer to "4.2 Volume Settings" in the manual.



3.3 Connect headphones / headset

Supports both 3.5 mm and 4.4 mm headphone jacks. The 3.5 mm jack is compatible with CTIA headsets.

Headset usage video tutorial:

<https://www.toppingaudio.com/supports?search=DX1+II&tab=video-tutorial>



4. Press the knob briefly to select your desired input



5. Output setting

Default output for all, no need to switch.

6. Turn down the volume



7. Play music and adjust the volume

